

## GENERAL DIRECTIONS

- Keep the radio away from excess heat and moisture.
- Direct contact with something very hot or long exposure to strong sunlight may damage the radio.
- When your car body is much over heated with strong sunlight, use the radio after cooling the body by driving your car for a while.
- In weak signal areas, pull out car antenna to its full length.
- Where signals are strong enough, insert the antenna into its receptacle.
- When the power antenna is damaged, please use the antenna designated by DATSUN.

## SPECIFICATIONS

CIRCUIT SYSTEM	All transistor superheterodyne with RF auto tuning system
TUNING RANGE	530~1,605 KHz
TRANSISTOR	8
IC	1
DIODE	5
THERMISTOR	2
POWER SUPPLY	DC 12V negative ground
CURRENT CONSUMPTION	100 mA (with no signal)
AUDIO OUTPUT	4 W
LOUDSPEAKER	5 1/8" PM 4ohms
ANTENNA	Power antenna (RO-74B) or Lock antenna (RO-16ZB)
WEIGHT	4 lbs. 6 oz.

# NISSAN MOTOR CORP.



## Hitachi, Ltd. Tokyo Japan

Head Office : 5, 1-chome, Marunouchi, Chiyoda-ku, Tokyo

Tel. Tokyo (212) 1111 (80 lines)

Cable Address : "HITACHI" TOKYO

Codes All Codes Used

# DATSUN genuine



## HITACHI

# CAR RADIO

## model TM-1081ZB



## OPERATING GUIDE